



## Real Wood Adhesive

### 1. Chemical Product and Company Data

**Product Name:** Real Wood Adhesive  
**Company Name:** Real Wood Floors  
**Product Use:** Wood Floor Adhesive  
**Generic Description:** Single-Component Urethane Wood Flooring Adhesive  
**General and MSDS assistance:** 877.215.1831

### 2. Composition and Ingredients

Component	CAS #	Weight %	OSHA(PEL)	ACGIH(TLV-TWA)
• Diphenylmethane diisocyanate	101-68-8	<1%	0.02	0.005 ppm
• Calcium Carbonate	1317-65-3	35 - 60%	15mg/m3	10 mg/m3

### 3. Hazards Identification

*Product reacts with water to release small amounts of carbon dioxide. Product is a skin and eye irritant. Product contains small amounts of MDI isocyanate and small amounts of mineral spirits. **KEEP OUT OF THE REACH OF CHILDREN.** Vapors are minimal at room temperature. Respiratory sensitization can occur due to residual MDI content.*

### 4. Emergency and First Aid Procedures

**Eyes:** Flush with large amounts of cool water for at least 15 minutes while holding eyelid open. Seek medical attention.  
**Skin:** Remove contaminated clothing. Wash area of contamination with soap and water. If rash or irritation or other symptoms persist, seek medical attention.  
**Inhalation:** Remove to fresh air. If breathing has stopped initiate artificial respiration and obtain immediate medical attention.  
**Ingestion:** Do not induce vomiting. Do not give anything by mouth. Seek immediate medical attention.

### 5. Fire Fighting Measures

**Flash Point:** >200 F      **Lower Explosive Limit:** N/A      **Upper Explosive Limit:** N/A

**Extinguishing Media:**  
 Dry chemical, foams or water spray, carbon dioxide.  
**Fire Fighting Procedures:**  
 Use self contained breathing apparatus and protective clothing.  
**Fire and Explosion Products:**  
 Combustion of this product may yield irritating or toxic gases.  
**HMS (Hazard Materials Identification System) Rating:**  
 Health – 1 Fire – 1 Reactivity – 0 Protection - B  
**Carcinogenicity:**  
 OSHA – NO / NTP – NO / IARC – NO

# MATERIAL SAFETY DATA SHEET

Urethane Wood Flooring Adhesive

**Likely Route of Entry into Body:** Skin contact.

**Contact:** May cause irritation to skin on direct contact which may result in a rash or reddening. May also cause skin sensitization and / or dermatitis.

**Ingestion:** May cause irritation, discomfort and vomiting. Do not induce vomiting. Seek immediate medical attention.

**Inhalation:** Risk of inhalation hazard is minimal. If it is perceived that inhalation may be causing irritation, remove to fresh air. If any form of irritation, dizziness or other effect persists, seek medical attention.

**Medical Conditions which May be Aggravated by Overexposure:**

Preexisting skin and respiratory conditions. Previously sensitized individuals may have allergic reactions.

## 6. Accidental Release Measures

**Spill or Leak Clean Up Procedures:**

While utilizing correct protective equipment, place spilled material into an appropriate container.

**Waste Disposal:**

Dispose of material in accordance with local, state and federal regulations.

## 7. Handling and Storage:

Store this product in a cool dry area, out of direct sunlight. Store in a well ventilated area away from all sources of ignition. Avoid contact with skin and eyes.

## 8. Exposure Controls and Personal Protection

**Ventilation:**

Use in well ventilated areas only to maintain PEL / TLV levels below set exposure limits.

**Respiratory Protection:**

Due to the low V.O.C. nature of this product, respiratory protection is not normally required. However, if PEL / TLV levels may potentially be exceeded, use NIOSH / MSHA approved respirator.

**Eye Protection:**

Wear safety glasses or goggles as necessary to protect eyes.

**Skin Contact:**

Protective gloves are recommended in situations when direct skin contact is unavoidable (nitrile, rubber or better).

**Other Protective Equipment:**

Use other types of equipment as needed to help minimize contact.

## 9. Physical and Chemical Properties

**Appearance and Odor:** Beige / creamy liquid / low odor

**Solubility in Water:** Insoluble

**Evaporation Rate** (Compared to Butyl Acetate as 1.0): <1.0 Boiling Point: >300F

**pH:** N/A

**Vapor Density** (Air = 1.0): >1.0

**Volatile Organic Content:** <30.0 g/l

**Vapor Pressure:** <1 mm Hg @ 75F / 24C

**Freezing Point:** N/E

# MATERIAL SAFETY DATA SHEET

Urethane Wood Flooring Adhesive

## 10. Stability and Reactivity

**Stability:**

Stable.

**Conditions to Avoid:**

Exposure to water will cure material. Long term exposure to elevated temperatures will increase viscosity of material.

**Materials to Avoid Contact with:**

Alcohols, acids, amines, water.

**Hazardous Decomposition products:**

Oxides of nitrogen and carbon, hydrocarbons, hydrogen cyanide.

## 11. Toxicological Information

Detrimental health effects are not expected as long as correct industrial hygiene and safety protocols are followed.

## 12. Ecological Information

This formulation has not been tested for environmental impacts.

## 13. Disposal Considerations

Dispose of material in accordance with local, state and federal regulations.

## 14. Transportation Information

**DOT:** Not regulated as a hazardous material.

**UN:** Not regulated as a hazardous material.

## 15. Regulatory Information

Contains	CAS Number	Percent
• Diphenylmethane diisocyanate	101-68-8	<1%

**TSCA:** All components in this product are listed except where written as exempt.

**Pennsylvania:** Hazardous component at 1% or greater: Mineral spirits.  
Non-hazardous at 3% or greater: reacted urethane prepolymer.

**New Jersey:** Reacted urethane prepolymer, mineral spirits (CAS 8052-41-3),  
Diphenylmethane diisocyanate (CAS 101-68-8).

## 16. Disclaimer

All information set forth herein is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy or completeness of this information. Real Wood Floors assumes no responsibility for personal injury or property damage to sellers, users or third parties caused by this material. Such sellers or users assume all risks associated with this material.